



METAGUARD | ALL-ROUND SAFETY

MAXECO RANGE

8061
Size: 3 - 13
Sex: Male
Colour: Black



COMPONENT SPECIFICATIONS

UPPER

- Cut from 1.9mm – 2.1mm Barton Print leather with PU collar and tongue.
- 10mm EVA padded collar and 10mm padded bellows tongue for enhanced comfort and ankle support.
- Heel stiffener for shape longevity.
- 4 pair brass D-rings for quick lacing and release.
- 110cm black braided nylon laces with central core for additional strength.
- Polypropylene metaguard for enhanced protection of the metatarsal bones.

LINING

- The vamp lining is made from non-woven synthetic fibre for enhanced comfort and breathability.
- The collar lining is made from black ferrabelle non-woven material for breathability.

TOE CAP

- Steel Toe Cap.
- Can withstand an impact load of 200 joules.

SOLE

- Shank reinforcement for additional arch support.
- The Maxeco sole is made from Double Density PU/PU.
- The midsole is made from a flexible low density Polyurethane with a shore hardness of 0.45mm – 0.50mm.
- The outer sole is made from a hardwearing Polyurethane with a shore hardness of 0.64mm – 0.65mm.
- The boot can withstand temperatures up to 95°C.
- The boot has SRA rated slip-resistance.
- The boot is anti-static.

IN-SOCK & TOP SOCK

- Anti-static in-sock is made from 2mm non-woven material.
- The top sock is made from a durable polyester material that offers abrasion resistance and is quick drying in nature. The top sock is treated with Ultra-Fresh technology to impart anti-bacterial and anti-static properties to the material. The top sock contains anti-static stitching and has been treated with a lemon scent for lasting freshness.

This Metaguard boot has been tested to comply with the SANS/ISO 20345 safety footwear specifications and carries this stamp of approval.

This product is manufactured at Bagshaw Safety Footwear, a division of BBF Safety Group (Pty) Ltd, which is an ISO 9001 accredited factory.