



LEMAITRE



www.lemaitre.co.za  
Made in South Africa

# SPECIFICATION SHEET




## NOMAD | COMFORT PARABOLIC RANGE

**8001**

Size: 5 - 12

Sex: Male

Colour: Black or brown



### UPPER

- Cut from 2.0mm – 2.1mm Barton Print leather with PU collar and tongue as well as reflective piping.
- 10mm EVA padded collar for enhanced comfort and ankle support.
- Heel stiffener for shape longevity.
- 4 pair brass D-rings for quick lacing and release.
- 110cm black or brown braided nylon laces with central core for additional strength.

### IN-SOCK & TOP SOCK

- Anti-static in-sock is made from 2mm non-woven material.
- The top sock is made from a durable polyester material that offers abrasion resistance and is quick drying in nature. The top sock is treated with Ultra-Fresh technology to impart anti-bacterial and anti-static properties to the material. The top sock contains anti-static stitching and has been treated with a lemon scent for lasting freshness.

### LINING

- The vamp lining is made from non-woven synthetic fibre for enhanced comfort and breathability.
- The counter lining is made from 0.8mm heel grip for enhanced stability to prevent the heel from slipping out the boot.

### TOE CAP

- Steel Toe Cap.
- Can withstand an impact load of 200 joules.

### SOLE

- Shank reinforcement for additional arch support.
- The Parabolic sole is made from Double Density PU/ PU with a concave curve to cushion impact.
- The midsole is made from a flexible low density Polyurethane with a shore hardness of 0.45mm – 0.50mm.
- The outer sole is made from a hardwearing Polyurethane with a shore hardness of 0.64mm – 0.65mm.
- The boot can withstand temperatures up to 95°C.
- The boot has SRA rated slip-resistance.
- The boot is anti-static.

This Nomad boot has been tested to comply with the SANS/ISO 20345 safety footwear specifications and carries this stamp of approval.

This product is manufactured at Bagshaw Safety Footwear, a division of BBF Safety Group (Pty) Ltd, which is an ISO 9001 accredited factory.