



LEMAITRE

SPECIFICATION SHEET



www.lemaitre.co.za
Made in South Africa



STRIKER | SLIP-RESISTANCE

APOLLO RANGE

8037

Size: 5 - 12

Sex: Male

Colour: Black



COMPONENT SPECIFICATIONS

UPPER

- Smooth Buffalo Full Grain leather – 1.9mm – 2.1mm.
- Durable black PU fabric in collar and tongue for comfort.
- 19mm padded collar and 10mm padded bellows tongue for enhanced comfort and ankle support
- Heel stiffener for shape longevity.
- 3 pair telescopic eyelets and 1 pair plastic eyelet inserts.
- 110cm black braided nylon laces with central core for additional strength.

LINING

- The vamp lining is made from non-woven synthetic fibre for enhanced comfort and breathability.
- The quarter and tongue lining are made from black ferrabelle non-woven material laminated to 4mm foam for enhanced comfort and breathability.

TOE CAP

- Steel Toe Cap.
- Can withstand an impact load of 200 joules.

IN-SOCK & TOP SOCK

- Anti-static in-sock is made from 2mm non-woven material.
- The top sock is made from a durable polyester material that offers abrasion resistance and is quick drying in nature. The top sock is treated with Ultra-Fresh technology to impart anti-bacterial and anti-static properties to the material. The top sock contains anti-static stitching and has been treated with a lemon scent for lasting freshness.

SOLE

- Shank reinforcement for additional arch support.
- The Apollo sole is made from Double Density PU/PU.
- The midsole is made from a flexible low density Polyurethane with a shore hardness of 0.45 – 0.50mm.
- The outer sole is made from a hardwearing Polyurethane with a shore hardness of 0.64mm – 0.65mm.
- The shoe can withstand temperatures up to 95°C.
- The shoe has SRC rated slip-resistance.
- The shoe is anti-static.

This Striker shoe has been tested to comply with the SANS/ISO 20345 safety footwear specifications and carries this stamp of approval.

This product is manufactured at Bagshaw Safety Footwear, a division of BBF Safety Group (Pty) Ltd, which is an ISO 9001 accredited factory.