



LEMAITRE
SAFETY FOOTWEAR



ALL-ROUND SAFETY **MAXIMUS** GLADIUS RANGE



STEEL TOE CAP | 8078

SOLE: GLADIUS SOLE | SIZE: 3-13

SEX: MALE

COLOUR: BLACK

THE MAXIMUS BOOT HAS BEEN TESTED
TO COMPLY WITH THE SANS/ISO 20345
SAFETY FOOTWEAR SPECIFICATIONS AND
CARRIES THIS STAMP OF APPROVAL.

FEATURES OF THE MAXIMUS:

UPPER

- Cut from 1.9mm – 2.1mm Barton print genuine leather upper with split leather collar and tongue.
- 10mm EVA padded collar and 10mm padded bellows tongue for enhanced comfort and ankle support.
- Heel stiffener for shape longevity.
- 4 pair brass D-ring for quick lacing and release.
- 110cm black and red braided nylon laces with central core for additional strength.
- Reflective inserts for increased visibility in low light.
- TPU heel support structure for reinforcement and additional strength.

IN-SOCK & TOP SOCK

- Anti-static in-sock is made from 2mm non-woven material.
- The top sock is made from a durable polyester material that offers abrasion resistance and is quick-drying in nature.
- The top sock is treated with Ultra-Fresh technology to impart anti-bacterial and anti-static properties to the material.
- The top sock contains anti-static stitching.

LINING

- The vamp lining is made from non-woven synthetic fibre for enhanced comfort and breathability.
- The counter lining is 0.8mm heel grip for enhanced stability to prevent the heel from slipping out the boot.
- The collar lining is made from black Cambrill non-woven material for breathability.

TOE CAP

- Steel Toe Cap.
- Can withstand an impact load of 200 joules.

SOLE

- Shank reinforcement for additional arch support.
- The Gladius sole is made from Double Density PU/PU.
- The midsole is made from a flexible low density polyurethane with a shore hardness of 0.45 – 0.50mm.
- The outer sole is made from a hardwearing polyurethane with a shore hardness of 0.64mm – 0.65mm.
- The boot can withstand temperatures up to 95°C.
- The boot has SR slip-resistance.
- The boot is anti-static.

**FROM ONE WORKER
TO ANOTHER**

